

PAROPY CL WATER SLIDE

APPLICATION INSTRUCTIONS

NOTES

Recommended Materials

White or Light Colored
Candles
Glass
Metal
Wood
Soap

Accessories Required

Computer, Color Laser
Printer, Large Water
bowl, Dish Soap, Plain
Paper, Plastic bag or
plastic wrap.

Printable side

The printable side is
the white glossy coated
side.

Storage

Paropy CL Water Slide
has an indefinite shelf
life when stored at
room temperature.
Keep away from direct
heat, sunlight, and
humidity.

Tips

For extra durability on
candles, we suggest
using a glue stick to
help adhere the WT
transfer paper.

The candle can also
be heated with a blow
dryer to soften the wax
before applying the
transfer.

STEP BY STEP

Paropy CL Water Slide will allow image transfer to objects that cannot be heated with a heat press.

This paper will work in most Oil and Non-Oil Laser Copiers and Printers. It is recommended that you do a test before commercial application.

Step 1

Feed transfer paper into laser printer so that the printer is printing on the printable side (white glossy coated side). It is recommended to use the bypass tray when printing.

Step 2

Design your image and and resize if necessary. Do not mirror image the design

Step 3

Trim the imaged Water Slide paper as close as possible without cutting into image using scissors/exacto knife.

Step 4

Fill suitable sized bowl with water and add about 5-10% liquid dish soap.

Step 5

Put a piece of plastic wrap on the counter or work surface. Put a little water from the bowl on the plastic wrap. Then place the imaged paper in bowl for 5-10 seconds.

Step 6

Put wet WT paper from the bowl on pre wet plastic bag/wrap face down. Absorb excess water with a plain piece of paper.

Step 7

Gently remove paper backing from plastic bag/wrap. Place the imaged plastic bag/wrap on top of material to be printed. With sponge and finger, gently correct position of image and iron out air bubbles.

Step 8

Let the transfer and material dry for at least 1 hour before handling.